

# CENTURY®

## *Midnight Express*



Composite Body and Other Optional Equipment Shown.

Ideally suited for high-volume towing, impound and repossession work, the Midnight Express is designed to be fast, easy and safe to operate. The driver can function the boom and hydraulic wheel lift from the safety and convenience of the cab and even pick up parallel parked vehicles at a 90° angle. Always remember to use your safety straps, safety chains, and tow lights before towing. Call 1-800-292-0330 or contact your local Century distributor for more information on the answer to high-volume towing the fast and easy way, the Midnight Express by Century.



The operator extends and lowers the wheel lift to the ground while backing up to the vehicle at a 90° angle.



As the low profile crossbar contacts the side of the tire it pivots around into position in front of the tires.



The operator now closes the arms around the tires and raises the vehicle without ever getting out of his truck. The operator is now ready to exit his truck and install the proper safety equipment.



# Legendary Leadership

## STANDARD FEATURES

- Integrated Boom & Wheel Lift System
- Century Express Hydraulic Hook-Up
- Clutch Pump
- In-Cab Remote Control Pendant on Cord with 10 Functions
- 1 Pair of Safety Straps
- Safety Chains in Rear Pockets
- Tool Compartments, Left & Right Hand Side
- Steel Light Pylon
- Adjustable Width Steel Modular Body
- Removable Access Plate for Hydraulic Valve Service
- 8,000 lb. Variable Speed Hydraulic Winch (301M)
- 3/8" x 100' Cable Assembly (301M)
- 360° Directional Boom End Swivel (301M)
- Federal Standard #108 Light Group
- Wiring Harness with Junction Box
- Mud Flaps
- Back-Up Alarm
- Power Fold for Stinger Storage
- Self Centering Crossbar with 3" Pivot Pin
- Trailer Hitch Attachment
- Pre-Assembled and Tested

## WHEEL-LIFT RATING

Lift Rating ..... 4,000 lbs.  
Tow Rating ..... 7,500 lbs.

## WHEEL-LIFT SPECIFICATIONS

Retracted Distance from Tailgate  
At Normal Tow Position ..... 50"

Extended Distance from Tailgate  
At Loading Position ..... 73"

Tow Hitch Rating ..... 5,000 lbs.

## OPTIONAL FEATURES

- Composite, Aluminum or Stainless Steel Body
- Switch Panel
- Motorcycle Attachment
- Lockable Go-Jak Storage Brackets
- Dolly Bunks
- Fuel & Trash Can with Storage Brackets
- Aluminum Tubular Light Pylon (Std. with Composite Body)
- Emergency Lighting
- Work Lights
- Front Push Bumper
- 24" Tunnel Toolbox for 84" C.A.
- Many other Century Midnight Express Options



Standard Steel Body with Optional Aluminum Tubular Pylon Shown.

## BOOM SPECIFICATIONS

At Boom End Swivel ..... 8,000 lbs.

## WINCH RATING & CABLE

Rating - First Layer of Drum ..... 8,000 lbs.  
Diameter and Length ..... 3/8" x 100'  
Type ..... 6 x 19 Hemp Center, IPS

## CHASSIS RECOMMENDATION

GVWR ..... 10,000 - 19,000 lbs.  
Minimum Cab to Axle (Clear) ..... 60"  
Maximum Cab to Axle (Clear) ..... 84"

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.

Right: Lockable Go-Jak Storage Brackets  
Below: Fuel & Trash Can with Storage Brackets  
Bottom Right: Dolly Bunks



**Miller**  
INDUSTRIES  
©2008 Miller Industries Towing Equipment Inc.

**CENTURY®**  
8503 Hilltop Drive • Ooltewah, TN 37363  
800-292-0330 • 423-238-4171  
FAX 423-238-5371 • www.MILLERIND.com

**DISTRIBUTED BY:**