



D.T.U.



"Detachable Towing Unit"



Some Optional Equipment May Be Shown.

The new Holmes D.T.U. (Detachable Towing Unit) offers proven design and technology from the oldest and most trusted name in the towing industry. The front legs allow the unit to be easily removed in a matter of minutes so your truck can be multi-functional for both towing or pulling trailers.

The D.T.U. is designed to secure to your truck using a front lock-down bracket and your Fifth Wheel Plate. The power for the unit is provided by an optional wet line kit, with quick connect couplers, which is installed on your truck. Other popular options include a 20,000- or 25,000-pound planetary winch, tool boxes and lanyard controls; all of which are available from your local Holmes distributor.



DETACHABLE TOWING UNIT

SPECIFICATIONS

Lift Capacity	
Retracted	35,000 lbs.
Extended	16,000 lbs.
Reach Past Tailboard	
Fully Extended	113 inches
Fully Retracted	51 inches
Power Tilt Arc.20°
Shipping Weight	
Without winch	4,550 lbs.
With 20,000 Winch	5,000 lbs.

STANDARD FEATURES & EQUIPMENT

- Power Elevation
- Power Extension
- Power Fold
- Power Tilt
- Front Stands
- Manual Controls
- 4 Sets of Frame Forks
- Fork Storage Holders
- Safety Chains
- Hook End Caps



OPTIONAL EQUIPMENT

- 20,000-lb. Planetary Winch
 150' x 9/16" IWRC Cable
- 25,000-lb. Planetary Winch
 200' x 5/8" IWRC Cable
(Winch Options Include: Air Tensioners, Air Free Spool, 360° Sheave Head, Air & Electrical Lines)
- Wet Line Kit
 PTO with pressure relief valve, pump, 15-Gallon Hydraulic Tank, Return Filter, Quick Disconnect, Fittings & Hoses
- Hand-Held Remote Control
 6-Function Controller with 25' Cord
- Emergency Lighting
- Work Area Lighting
- Remote Tailboard Control
- Switch Panel
- Tow Lights & Cord
- Tool Compartment
- Additional Lift Forks & Towing Attachments



Note: Some optional equipment may be shown. Other Holmes Towing & Recovery Equipment is Available from your local Holmes Distributor.

CHASSIS RECOMMENDATIONS

Minimum Wheelbase 250"

Min. Clearance from front of D.T.U. to Center of Trunnion 84"

Note: Ratings are based on structural factors only - not chassis capacity. All chassis specifications are minimums, heavier specifications may be required depending on chassis and equipment weights. Holmes reserves the right, without notice and without obligation, to improve or modify products, which may change the specifications, models and feature availability.



Proven Design & Technology



© 2010 Miller Industries Towing Equipment Inc. All Rights Reserved.

8503 Hilltop Dr. • Ooltewah, TN 37363
 Phone: (800) 489-2401 • (423) 238-4171
 Fax: (800) 960-6667
www.millerind.com

DISTRIBUTED BY: