



# *Delivering The Difference*

**Model 135/150**



**LANDOLL 135/150**

*Fixed Gooseneck Beavertail*


# Standard & Optional Equipment/Features—Model 135/150 Fixed Gooseneck Beavertail

S=Standard O-Optional

Model 150	50 Ton	100,000#
Model 135	35 Ton	70,000#
<b>MAINFRAME</b>		
- Fabricated 80,000 # PSI	S	S
- Four Beam Design	S	S
- Capacity—70,000# Distributed / 50,000# Concentrated in 10'	S	
- Capacity—100,000# Distributed / 70,000# Concentrated in 10'		S
<b>KINGPIN SETTING</b>		
- 18" Setting	S	S
- 86" Swing Clearance	S	S
<b>CROSSMEMBERS</b>		
- 4" Jr. I-Beam on 12" Centers	S	S
<b>DECK &amp; FEATURES</b>		
- 102" Wide	S	S
- Lower Deck Length		
135—23'7", 26'7", 28'7", 31'7"	S	S
150—28'7", 31"7"	S	S
- 90 Degree Slope Drop	S	S
- 37¼" Deck Height (Loaded)	S	S
- 1¾" Nominal Apitong (Lower Deck)	S	S
- 20" Loaded Ground Clearance	S	S
<b>UPPER DECK WINCH OPTIONS:</b>		
- 12,000 lb. Worm Gear	O	O
- 15,000 lb. Planetary Winch	O	O
- 20,000 lb. Worm Gear Winch	O	O
- Remote Control Single Function—Street & Curb Rear	O	O
- Cable Roller Guide for Winch—12,000 lb., 15,000 lb. Or 20,000 lb. Slope or Upper Deck	O	O
<b>TIE DOWNS/CHAIN GOTCHAS</b>		
- Double Key Hole Chain Slots on 24" centers	S	S
- "D" Ring Bolt on at Winch (each) (Two Locations Available)	O	O
- Flush Mounted "D" Rings (each)	O	O
<b>TOOLBOX</b>		
- Storage Area Upper Deck 23"x 35"x 8" without lid	S	S
<b>DECK ACCESSORIES</b>		
- Lower Deck Lockable Tool Box (Curb Side or Street Side) (42" wide x 28" deep x 9" high)	O	O
- Lockable Lid for Storage Area	O	O
- 96" Width Not Available		
<b>SLOPE RAMP</b>		
- 5 Ft. Aluminum Ramps (Portable) 8,000 lb. Capacity Each	O	O
- Upper Deck Ramp (Air Operated)	O	O
- Landoll Traction Ramps (Steel)	O	O
<b>BULKHEADS</b>		
- 16"/24" 2-Position Bulkhead/Front Extension (Solid)	O	O
- 48" High Mesh 102" or 96" Wide	O	O
- Bolt on Binder Storage Rack for 48" Bulkheads	O	O
- Halogen Work Light-Dual (Mounted on Bulkheads)	O	O
- Spare Tire Carrier 48" Bulkhead Front Mounted	O	O
- Spare Tire Carrier 48" Bulkhead Rear Mounted	O	O
- Dual Spare Tire Carrier 48" Bulkhead, Front Mounted	O	O
<b>PARKING STANDS</b>		
- Pin Drop (in lieu of standard)	O	O
<b>AXLES</b>		
- (2) 25,000 Tandem Dual Tire, Oil Bath Bearings	S	
- (3) 25,000 Tandem Dual Tire, Oil Bath Bearings		S
<b>SUSPENSION</b>		
- Multi-Leaf Springs 45,000 capacity	S	
- Multi-Leaf Springs 67,200 capacity H9700/60" Spread		S
- Neway Air Ride RLU228 22,500# Capacity with Manual	O	O

Specifications subject to change without notice or obligation.

Model 150	50 Ton	100,000#
Model 135	35 Ton	70,000#
<b>BRAKES</b>		
- Automatic Slack Adjusters	S	S
- 12.25 x 7.5 Full Air w/spring Brakes One Axle		
- ABS, Rockwell 4S2M	S	S
<b>OIL SEAL HUBS</b>		
- Internal Mated Assembly	S	S
<b>TIRES/WHEELS</b>		
- 10R 17.5 Goodyear LRH	S	S
- Hub Pilot/Steel Outboard Brake Drum	S	S
<b>RIMS</b>		
- 17.5 x 6.75 Tubeless	S	S
- 17.5 Aluminum wheels (8 Bolt Polished)	O	O
<b>TIRES &amp; RIMS</b>		
- Spare Goodyear Tire & Hub Pilot Type Rim (21570R 17.5)	O	O
- Spare Goodyear Tire & Hub Pilot Type Rim (10R 17.5)	O	O
- 10R 17.5 Michelin in Lieu of Standard Goodyear	O	O
- Spare Michelin Tire & Hub Pilot Type Rim (10R 17.5)	O	O
- 235/75R 17.5 Bridgestone Tires in Lieu of Standard Goodyear	O	O
- Spare Bridgestone Tire & Hub Pilot Type Rim (235/75R 17.5)	O	O
- 215/70R 17.5 Michelin Tires in Lieu of Standard Goodyear	O	O
- Spare Michelin Tire & Hub Pilot Type Rim (215/70R 17.5)	O	O
- Hubmeter	O	O
- 255/70R 22.5 Goodyear Tires in Lieu of Standard Goodyear	O	O
<b>HYDRAULIC POWER SOURCE</b>		
- Air Shift PTO & Wet Kit for Tractor—Not Installed (30 Gallon Tank Required)	O	O
- Installation of PTO & Wet Kit (Control)	O	O
- Hydraulic Quick Couplers 1 Male/1 Female (Matches Trailer) (Part # 105902)	O	O
<b>HYDRAULIC HOOK UP</b>		
- Hydraulic Quick Couplers 2500 PSI/17 GPM	O	O
<b>AIR/ELECTRICAL CONNECTION</b>		
- 7 Way Receptacle (Electrical)	S	S
<b>LIGHTS</b>		
- Light Tail System, Sealed Beam Grommet Mounted with Sealed Wiring Harness, Center Mounted Turn Signal	S	S
<b>FINISH/COLOR</b>		
- Steel Grit Shot Blast to Bright Metal	S	S
- Epoxy Primer	S	S
- Acrylic Urethane White, Black, Yellow, Blue, Red, Green	S	S
<b>WEIGHT</b>		
- 135-40 12,000	S	
- 150-48 14,500		S
<b>BEAVERTAIL</b>		
- 68" Self-Cleaning Beavertail	S	S
- Apitong Wood Covered Beavertail	O	O
- Traction Bars for Wood Covered Beavertail	O	O
<b>RAMPS</b>		
- 5' Self-Cleaning Adjustable Spring Assisted Flipover	S	S
- Heavy Duty Crawler Ramp (Wood Filled)	O	O
- Third Ramp—Self-Cleaning or Wood Filled	O	O



Delivering The Difference! Visit us at [www.landoll.com](http://www.landoll.com)



Call 1-800-428-5655 for your BEST hauling solutions!

1900 North Street • Marysville, KS 66508 • Ph. 785-562-5381 • FAX 785-562-4893