



*Delivering
The
Difference*

Model LT1016



LANDOLL® LT1016

Tilt Utility Trailer

Standard & Optional Equipment/Features - Tilt Utility Tag

S=Standard O-Optional Blank=N/A

LT1016 Tilt Deck	
DIMENSIONS	
- 16' Flat Deck	S
- 22" Loaded	S
- 80" Wide between fenders	S
- 102" O/A Width	S
CAPACITY	
- 10,000#	S
- 3,150# Trailer Weight	S
- 13,150# GVWR	S
MAIN FRAME	
- 6" Channel	S
- 4" Jr. I-Beam 80,000 PSI Yield on 24" Centers	S
- 6" Channel Hitch Frame	S
- Tool Box in Hitch	S
AXLES	
- 2 - 6,000#, Torflex, E-Z Lube	S
TIRES & BRAKES	
- LT235/85R16LRE	S
- Both Electric Brakes	S
DECK	
- 2" CA-B (Copper Azole) Treated Pine	S
- (4) 5/8" D-Rings	S
- Stake Pockets 2 per Side	S
- Sideboards	O
TILTDECK	
- 2-1/2" x 16" Cushion Cylinder	S
- Approach Plate - Full Width	S
- Tilt Angle - 12-1/2 degrees	S
ACCESSORIES	
- Fenders - H.D. 14 gauge w/Back	S
- Running Boards - w/Anti-Skid Tape	S
- White, Black or Yellow Powder Coat Paint	S
PHOTOS MAY SHOW OPTIONAL EQUIPMENT	



A full width rear light bar and Landoll traction plate makes loading small wheel machines efficient.



The cushion cylinders tilt the bed to ground load position and back to transport position smoothly.



The hitch adjusts from 12" to 24" vertically.



Loading angle as low as 12 1/2 degrees.



A heavy duty bed lockdown with safety latch firmly secures the bed in transport position.



14 gauge molded fenders and anti-slip steps for strength and safety.



A 6"channel iron frame under the main frame for superior strength. A solid formed 6" height headboard for protection. (Stake pockets shown for optional removable sideboards.)



Delivering The Difference! Visit us at www.landoll.com

Call 1-800-428-5655 for your BEST hauling solutions!

1900 North Street • Marysville, KS 66508 • Ph. 785-562-5381 • FAX 785-562-4893

Remember: Quality is Always a Bargain!

LT1016-0704