



Delivering The Difference

**Model
1020/1016+4**



LT1016+4/LT1020



Tilt Utility Trailers

Standard & Optional Equipment/Features—Tilt Utility Tag

S=Standard O=Optional

LT1020 Tilt Deck		
LT1016+4 Tilt Deck		
DIMENSIONS		
- 16' Flat Deck and 4' Stationary	S	S
- 20' Flat Deck	S	S
- 22" Loaded Deck Height	S	S
- 80" Wide between fenders	S	S
- 102" O/A Width	S	S
CAPACITY		
- 10,000#	S	S
- 3,500# Trailer Weight	S	S
- 13,500# GVWR	S	S
MAIN FRAME		
- 6" Channel	S	S
- 4" Jr. I-Beam Crossmembers	S	S
- 6" Channel Hitch Frame	S	S
- Tool Box Under Deck	S	S
AXLES		
- 2 - 6,000#, Torflex, E-Z Lube	S	S
TIRES & BRAKES		
- LT235/85R16LRE	S	S
- 12" X 2" Electric Brakes	S	S
DECK		
- 2" Treated Pine	S	S
- (6) 5/8" D-Rings	S	S
- (4) 5/8" D-Rings	S	S
- Stake Pockets 4 per Side	S	S
- Sideboards	O	O
TILT DECK		
- 2-1/2" x 16" Cushion Cylinder	S	S
- Tilt Control Valve System	O	S
- Approach Plate Landoll Traction Plate	S	S
- Load Angle - 10°	S	S
ACCESSORIES		
- Fenders - HD 14 Gauge w/Back	S	S
- Running Boards w/Anti-Skid Tape	S	S
- Yellow Powder Coat Paint	S	S
- Black or Red Powder Coat Paint	O	O
- Spare Tire Carrier	O	O



A full width rear light bar for added safety protection with machined safety approach plate.



Landoll's tilt control system and the 2-1/2" x 16" cushion cylinder can hold the deck in a tilted position or smoothly return the deck to transport position.



Adjustable hitch 12" to 24" vertically, plus 7,000 lb. drop leg jack are standard equipment.



Loading angle as low as 10°.



A heavy duty bed lockdown with safety latch firmly secures the bed in transport position.



Exclusive Landoll traction plate for superior traction while loading rubber tired and small wheeled equipment on the approach plate.



A 6" channel iron frame under the main frame for superior strength. A solid formed 6" height headboard for protection. (Stake pockets shown for optional removable sideboards)

Pictures may show optional equipment.

Delivering The Difference! Visit us at www.landoll.com



Call 1-800-428-5655 for your BEST hauling solutions!

1900 North Street • Marysville, KS 66508 • Ph. 785-562-5381 • FAX 785-562-4893

Remember: Quality is Always a Bargain!

LT1016-1000