

CENTURY[®]

10 Series - 3 Car Carrier



Some Optional Equipment Shown.

As the cost of fuel, parts, labor, and general maintenance increases you need to maximize your equipment's pay load per mile. With Century's 3 Car Carrier you can do just that. Century's proven 10,000 lb. 10 Series steel & aluminum carrier decks (available in 21' & 22' bed lengths) combines an independent wheel lift and an over-the-cab deck for the perfect package in multi-vehicle hauling. Century's blend of our trusted heavy-duty carrier bed and expertly engineered multi-vehicle design will be a profitable addition to your fleet.

*The Solution for Your
Multi-Vehicle Transportation Needs*

Legendary Leadership

BED SPECIFICATIONS

MAIN DECK

Load Rating	*10,000 lbs.
Minimum Loading Angle	**12.5°
Platform Length	21' or 22'
Platform Width: Inside Rails	91.5"
Outside Rails	96"
Platform Extension	108"
Winch Rating	8,000 lbs.
Cable	3/8" x 50' / 6 x 19 IPS

UPPER DECK

Load Rating	*5,000 lbs.
Platform Length	13'6"
Platform Width: Inside Rails	97"
Outside Rails	101"
Winch Rating	8,000 lbs.
Cable	3/8" x 75' / 6 x 19 IPS

* The ratings specified are based on structural factors only - not vehicle capabilities or capacities. Platform rating is based on an equally distributed load.

** Minimum load angle will change with chassis frame height.

WHEEL LIFT SPECIFICATIONS

Wheel Lift Rating	3,000 lbs.
Tow Bar Rating	5,000 lbs.

STANDARD FEATURES

- Available in Steel or Aluminum
- Consolidated Tilt & Full Length Mounting Frame
- Full Length Nylatron Slide Pads
- Solid Side Rails
- Independent Hydraulic Wheel Lift with Slide-In L-Arms
- Anti-theft Tailboard L-Arm Storage
- 8,000 lb. Hydraulic Winch & Cable
- LED Federal Standard 108 Lighting
- Black Acrylic Urethane Paint (Steel Only)
- Adjustable Rear Stabilizer
- Positive Lock-Down System
- Bed Anti-Tilt Feature
- Dual Illuminated Controls
- Dual Lift Cylinders
- One Extension Cylinder
- Hydraulic Pump
- Winch Clutch Release
- Winch Cable Tensioners
- Tow Light Plug
- 6 Key Slots
- Safety Chains
- Mud Flaps

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.

CHASSIS RECOMMENDATIONS

Minimum Single Axle Chassis Rating	
Front Axle 10,000 lbs., Rear 19,000 lbs.	
Minimum GVWR	29,000 lbs.
Minimum Cab to Axle (Clear)	
21'	154"
22'	166"
Maximum Frame Height	39"

NOTE: The outside frame rails of the chassis extending behind the cab must be free of fuel tanks, air tanks, battery boxes, exhaust racks, etc.

OPTIONAL FEATURES

- PTO
- 8,000 lb. Planetary Winch (Required)
- Tool Compartments
- Galvanized Subframe
- Additional Key Slot Package
- Removable Rails
- 3-Way Pivoting L-Arm System
- Smooth Floor in Lieu of Diamond Plate (Steel Only)
- Wired or Wireless Winch Remote
- Switch Panel
- Body Built 102" Wide
- Autoload Wheel Lift
- Independent Hydraulic Tow Bar
- Work Area Lighting
- Retractable Deck Ladder
- Many other Popular Century Options



The deck over the cab tilts hydraulically for easy loading and unloading.

