



Proven Solutions



LANDOLL 334/336
CAR CARRIER





Investing In The Future...

® **HIGH VOLUME.....EFFICIENT.....**

► Low Load Angle - 8° Lower Deck 17° Upper Deck



► Take a serious look at the Landoll 334/336 car trailer. This trailer is ideal for moving a large volume of vehicles, decreasing time and manpower, thus increasing efficiency and return on investment.

► Dump Angle - 18° Lower Deck, 28° Upper Deck



Landoll 334/336

.....DURABLE.....MANEUVERABLE



❖ Rugged Guide Rails on Lower and Upper Decks



❖ The Adjustable Upper Deck Allows for Easy Transition from Trailer to Overcab



❖ Cordless Hydraulic Controls



❖ Hydraulic Adjustable 24" Vertical Travel



❖ Manual Hydraulic Controls



❖ Tilt Cylinder - Major Steel Components Powder Coated

Standard & Optional Equipment/Features

Model 334 (4 car) / 336 (6 car) Car Carrier

S=Standard O=Optional

Model		334	336
Main Frame	Full Aluminum Extrusion Heat Treated	S	S
Crossmembers	9" Aluminum Floor Plate with Extruded Integral Crossmembers on 3" Centers	S	S
Parking Stands	Pin Drop	S	S
Axles	1-25,000# Dual Tire, Oil Bath Bearings 2-25,000# Dual Tire, Oil Bath Bearings	S	S
Suspension	Neway RLU228 Air Ride 22,500# Capacity	S	S
Brakes	12.25x7.5 Full Air Spring Brake ABS, 2S1M 12.25x7.5 Full Air Spring Brake ABS, 4S2M	S	S
Pin Setting	34" 15"	S	S
Swing Clearance	55" 75"	S	S
Width	102"	S	S
Length	35" 48"	S	S
Tie Downs	8 "D" Rings-6 Key Holes on Each Approach	S	S
Color	Metal Parts Powder Coated Black	S	S
Hydraulic Winch	4-Worm Gear 8,000# with 65' 3/8" Cable 6-Worm Gear 8,000# with 65' 3/8" Cable Winch Deduct-Per Winch-Maximum of Two May Be Deducted	S O	S S
Top Deck Adjustment Cylinder	4 Rephase for Level Lift 6 Rephase for Level Lift	S	S
Load Angle	Minimum 8° Lower Deck Minimum 17° Upper Deck Maximum 18° Lower Deck Maximum 28° Upper Deck	S S S S	S S S S
Upper Deck	Hydraulic Adjustable 24" Vertical Travel with Safety Lock on 2" Increments	S	S
Hydraulic Controls	Wireless Remote on Manual Controls on all Functions with Hand Held Control Box and Shoulder Strap	S	S
Over the Cab Installation	One Car Over Cab can be Installed on a Variety of Trucks (Contact Factory). Others Subject to Surcharge. Installation of One Car Over Cab on Other than Above Chassis Installation of Safety Buzzer-In Cab for One Car Over Cab	O	O O O
Accessories	Left Hand Tool Box In-Cab Holder Control Box with Safety Buzzer Automatic Slack Adjusters Bridle Adapter Plate (each) Combination Chain (each)	S S S O O	S S S O O



Maximum Clearance 81"



One Winch per Vehicle Upper and Lower Deck



Adequate Clearance on Wide Variety of Vehicles

*Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight ratings (GAWR) or state and federal regulations.



Specifications subject to change without notice. Pictures may show optional equipment.

Call 1-800-428-5655 for Proven Solutions for your Hauling needs

1900 North Street • Marysville, KS 66508 • Ph 785-562-5381

Fax 785-562-4893 • www.landoll.com

Remember: Quality is Always a Bargain!

