

# CENTURY®

## *Express Series*



Composite Body and Other  
Optional Equipment Shown.

The Century Express is your answer to high volume towing the easy way. With Century's auto-loading, low profile crossbar design, you can easily pick up low clearance automobiles without getting out of your truck. The sloped tail board design gives you the best visibility of any autoloader in the industry. The 311 and 312 Express expands your vehicle capabilities with an extendable boom for light recovery work. Visit your local Century Distributor to see how the Century Express surpasses the competition.

## **Parallel Parked Autos...No Problem!**



The operator extends and lowers the wheel lift to the ground while backing up to the vehicle at a 90° angle.



As the low profile crossbar contacts the side of the tire it pivots around into position in front of the tires.



The operator now closes the arms around the tires and raises the vehicle without ever getting out of his truck. The operator is now ready to exit his truck and install the proper safety equipment.



# Legendary Leadership

## STANDARD FEATURES

- Integrated Boom & Wheel Lift System
- Century Express Hydraulic Hook-Up
- Clutch Pump
- In-Cab Remote Control Pendant on Cord with 8 Functions
- Dual Manual Controls
- 1 Pair of Safety Straps
- Safety Chains in Rear Pockets
- Tool Compartment, Left & Right Hand Side
- Adjustable Modular Body
- Power Boom Elevation with Holding Valve
- 8,000 lb. Variable Speed Hydraulic Winch (Dual Winches on the 312)
- 3/8" x 100' Cable Assembly
- 360° Directional Boom End Swivel
- Winch Cable Tensioner & Free Spool Handles
- Federal Standard #108 Lighting
- Wiring Harness with Junction Box
- Mud Flaps
- Tailboard Mounted D-Rings
- Back-Up Alarm
- Power Fold for Stinger Storage
- Self Centering Crossbar with 3" Pivot Pin
- Roller Guided Hose Tracking System



## WHEEL-LIFT SPECIFICATIONS

Retracted Distance from Tailgate	
At Normal Tow Position	52"
Extended Distance from Tailgate	
At Normal Tow Position	85 1/2"
Maximum Hydraulic Extension	33 3/4"
Lift Rating	4,000 lbs.
Tow Rating	7,500 lbs.

## BOOM SPECIFICATIONS

Century 301 Express	
At Boom Swivel	16,000 lbs.
Maximum Boom Elevation	33°
Century 311/312 Express	
Lift Height at Maximum Elevation	
Retracted	78"
Extended	111"
Reach Past Tailgate	
Minimum Elevation (Extended)	50"
Maximum Elevation (Extended)	22"
Boom Rating at Boom Swivel	
Retracted	16,000 lbs.
Extended	4,000 lbs.

## WINCH RATING & CABLE

Rating (first layer of drum) each Winch	8,000 lbs.
Diameter and Length (each winch)	3/8" x 100'
Type	6 x 19 Hemp Center, IPS



## OPTIONAL FEATURES

- Composite, Aluminum or Stainless Steel Body
- Tow Sling (311 & 312 only)
- Trailer Ball Adapter
- Motorcycle Attachment
- Aluminum Tubular Light Pylon
- Steel Light Pylon
- Go-Jak Mounting Brackets
- Fuel & Trash cans with Mounting Brackets
- Dolly Bunks
- Emergency Lighting
- Work Lights
- Front Push Bumper
- 24" Tunnel Toolbox for 84" C.A.
- Other Popular Century Options

## CHASSIS RECOMMENDATION

GVWR	15,000 - 19,000 lbs.
Minimum Cab to Axle (Clear)	60"
Maximum Cab to Axle (Clear)	84"

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.