

# CENTURY<sup>®</sup>

## *Light-Duty Conventional*



Composite Body and Optional 24" Tunnel Box Shown

After leading the industry for more than 25 years, the new Century line of light-duty towing and recovery units has once again raised the bar for quality, design and function. The new adjustable-width modular bodies are available in a wide choice of materials, including carbon or stainless steel, aluminum, or the sleek and stylish composite. The low-profile recovery booms are fabricated from four plates of high-tensile steel to save weight without sacrificing strength. For increased driver convenience, features such as tailboard L-arm storage, easy-access safety chain pockets and easy-to-operate dual control stations -- along with Century's proven wheel lift system -- are just a few of the many reasons why you should contact your local Century distributor.

# Legendary Leadership

## BOOM SPECIFICATIONS

Model	Boom Structural Rating (S.A.E.)		Maximum Angle	Boom Elevation Cylinder(s)	Maximum Hook Height (inches)	Reach Past Tailboard at Minimum Boom Angle (inches)
	Retracted 34°	Extended 34°				
411/412	16,000 lbs.	4,000 lbs.	48°	Single	173.5"	81.5"
602	20,000 lbs.	6,000 lbs.	45°	Dual	167.5"	81.5"
612	24,000 lbs.	8,000 lbs.	45°	Dual	167.5"	81.5"

## UNDERLIFT SPECIFICATIONS

Model	Tow Rating	Retracted Distance from the Tailboard	Extended Distance from the Tailboard	Lift Capacity at Full Extension	Lift Capacity Retracted with Forks	Underlift Tilt
411/412	7,500 lbs.	35"	67"	4,000 lbs.	N/A	+14° / -16°
602/612	20,000 lbs.	30"	66"	6,000 lbs.*	9,000 lbs.	+10° / -18°

\* With Lift Forks or Optional 6,000 lb. L-Arms.

## WINCH RATING & CABLE

Model	Winch Capacity	Winch Type	Cable Specifications
411	8,000 lbs.	Worm	3/8" x 100' 6x19 I.P.S.
412	(2) 8,000 lbs.	Worm	3/8" x 100' 6x19 I.P.S.
602	(2) 8,000 lbs.	Worm	3/8" x 100' 6x19 I.P.S.
612	(2) 12,000 lbs.	Worm	7/16" x 150' 6x25 I.W.R.C.

## STANDARD FEATURES

- 3-Way Pivoting L-Arm System
- 4,000 lb. Lightweight L-Arms
- Adjustable Width Modular Body, 88" or 94"
- 60" Cab-to-Axle Steel Body
- Drivers & Passenger Side Tool Compartments
- Tailboard D-Rings
- Tailboard Safety Chain Pockets
- Wheel Lift Safety Chains - 5/16, Grade 70
- L-Arm Storage Pockets
- Dual Boom & Wheel Lift Controls
- Independent Wheel Lift Tilt
- Winch Cable Tensioner(s) & Free Spool Handles
- Mud Flaps
- Federal Standard 108 Lighting
- 1 Set of 3" Low Profile Frame Forks and Holders(602/612)

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.



Optional aluminum body with 2 optional tunnel boxes

Century's new modular-body conventional units feature a fabricated low-profile boom for increased rear visibility. The Century 602 and 612 have dual boom lift cylinders for more power and stability during recovery applications.



## OPTIONAL FEATURES

- Aluminum Modular Body
- Stainless Steel Modular Body
- Composite Modular Body (94" Wide Only)
- Tunnel Box
- 6,000-lb. L-Arms (602/612)
- Emergency Lighting
- Tow Sling
- Dress-up Packages
- Trailer Hitch
- PTO
- Light Pylon
- Aluminum Tubular Light Pylon (25" & 33")
- Fold Down Light Bar Brackets
- Scotch Blocks
- Convenience Packages (Rails & Steps)
- Dollies

**Miller**  
INDUSTRIES  
©2010 Miller Industries Towing Equipment Inc.

**CENTURY®**

8503 Hilltop Drive • Ooltewah, TN 37363  
800-292-0330 • 423-238-4171  
FAX 423-238-5371 • www.MILLERIND.com

DISTRIBUTED BY: