

Delivering The Difference Model LT1020 LT1016+4



Tilt Utility Trailers

Standard & Optional Equipment/Features—Tilt Utility Tag

S=Standard O-Optional

LT1020 Tilt Deck		
LT1016+4 Tilt Deck		
DIMENSIONS - 16' Flat Deck and 4' Stationary - 20' Flat Deck - 22" Loaded Deck Height - 80" Wide between fenders - 102" O/A Width	\$ \$ \$ \$ \$	S S S S
CAPACITY - 10,000# - 3,500# Trailer Weight - 13,500# GVWR	\$ \$ \$ \$ \$	S S S
MAIN FRAME - 6" Channel - 4" Jr. I-Beam Crossmembers - 6" Channel Hitch Frame - Tool Box Under Deck	\$ \$ \$ \$ \$ \$ \$	\$ \$ \$ \$ \$
AXLES - 2 - 6,000#, Torflex, E-Z Lube	s	S
TIRES & BRAKES - LT235/85R16LRE - 12" X 2" Electric Brakes	s s	S S
DECK - 2" Treated Pine - (6) 5/8" D-Rings - (4) 5/8" D-Rings - Stake Pockets 4 per Side - Sideboards	s s o	S S S
TILT DECK - 2-1/2" x 16" Cushion Cylinder - Tilt Control Valve System - Approach Plate Landoll Traction Plate - Load Angle - 10°	s O S S	S S S S
ACCESSORIES - Fenders - HD 14 Gauge w/Back - Running Boards w/Anti-Skid Tape - Yellow Powder Coat Paint - Black or Red Powder Coat Paint - Spare Tire Carrier	S S S O O	S S O O



A <u>full width</u> rear light bar for added safety protection with machined safety approach plate.



Adjustable hitch 12" to 24" vertically, plus 7,000 lb. drop leg jack are standard equipment.



A heavy duty bed lockdown with safety latch firmly secures the bed in transport position.



Landoll's tilt control system and the $2-1/2" \times 16"$ cushion cylinder can hold the deck in a tilted position or smoothly return the deck to transport position.



Loading angle as low as 10°.



Exclusive Landoll traction plate for superior traction while loading rubber tired and small wheeled equipment on the approach plate.



A 6"channel iron frame under the main frame for superior strength. A solid formed 6" height headboard for protection. (Stake pockets shown for optional removable sideboards)

Pictures may show optional equipment.

Delivering The Difference! Visit us at www. landoll.com



Call 1-800-428-5655 for your BEST hauling solutions!

1900 North Street • Marysville, KS 66508 • Ph. 785-562-5381 • FAX 785-562-4893

Remember: Quality is Always a Bargain!